DESCRIPTION

Brass is an alloy mainly consisting of copper and zinc. Brass alloys can be easily shaped and are available in various colors. Brass has high thermal conductivity. CZ129 forging brass alloys have good forgeability. They are available in the form of rod. The following datasheet gives details about CZ129 brass alloys.

CHEMICAL COMPOSITION

Elements	Min (%)	Max (%)		
Cu	58.50	61.00		
Pb	0.80	1.50		
Fe	-	0.20		
Total Others Excl. Fe	-	0.50		
Zn	Remainder			

MECHANICAL PROPERTIES ACCORDING TO BS2874 (AS PER TEMPER M)

Range (mm)	From	То	UTS Min (N/mm²)	PS Min	Elongation Min (%)	Hardness Min	Hardness Max
	1.5	18.00	380.00	-	25.00	-	-
Round (Dia)	18.00	40.00	380.00	-	25.00	-	-
	40.00	75.00	350.00	-	28.00	-	-
	3.00	18.00	380.00	-	25.00	-	-
Hex (A/F)	18.00	40.00	380.00	-	25.00	-	-
	40.00	70.00	350.00	-	28.00	-	-
	3.00	18.00	380.00	-	25.00	-	-
Square (A/F)	18.00	40.00	380.00	-	25.00	-	-
	40.00	60.00	350.00	-	28.00	-	-
	3.00	18.00	380.00	-	25.00	-	-
Rectangle (Thickness)	18.00	40.00	380.00	-	25.00	-	-
	40.00	50.00	350.00	-	28.00	_	-

PHYSICAL PROPERTIES

	C. 1	
	Melting Point - Liquidus°F	1640
Ĭ	Melting Point - Solidus°F	1620
	Densitylb/cu in. at 68°F	0.305
772	Specific Gravity	8.44
	Electrical Conductivity% IACS at 68°F	27
	Thermal ConductivityBtu/ sq ft/ ft hr/ °F at 68°F	69
177.	Coefficient of Thermal Expansion 68-57210-6 per °F (68 – 572°F)	11.5
	Specific Heat CapacityBtu/ lb /°F at 68°F	0.09
1	Modulus of Elasticity in Tensionksi	15000
	Modulus of Rigidityksi	5600
-		

FABRICATION PROPERTIES

4	Technique	Suitability
	Soldering	Excellent
	Brazing	Good
7/	Oxyacetylene Welding	Not Recommended
	Gas Shielded Arc Welding	Not Recommended
ć	Coated Metal Arc Welding	Not Recommended
	Spot Weld	Not Recommended
	Seam Weld	Not Recommended
Ç,	Butt Weld	Fair
	Capacity for Being Cold Worked	Poor
	Capacity for Being Hot Formed	Excellent
	Forgeability Rating	100
	Machinability Rating	80
	Machinability Rating	80

- Builders Hardware
- > Building
- Consumer
- Electrical
- Industrial